Product Details

Product Range	Commercial Natural Stone
Texture Finish	Polished
Colours	Austral Coffee, Austral Juperana, Garnet Ice, Desert Brown, Desert Rose, Austral Verde & Austral Black
Product Code	
Format	Single Groove Bullnose
Place of Manufacture	-
Length (mm)	-
Width (mm)	-
Height (mm)	-
Size	
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f 'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	No
Declare	Yes
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf 36: 240 minutes. Please note FRL applies up to 3m high - restrained on to

Product Details

Product Range	Commercial Natural Stone
Texture Finish	Exfoliated
Colours	Austral Coffee, Garnet Ice, Desert Rose, Austral Verde, Desert Brown, Austral Juperana & Austral Black
Product Code	
Format	Shark Nose Bullnose
Place of Manufacture	-
Length (mm)	-
Width (mm)	-
Height (mm)	-
Size	
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f 'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	No
Declare	Yes
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf 36: 240 minutes. Please note FRL applies up to 3m high - restrained on to

Product Details

Product Range	Commercial Natural Stone
Texture Finish	Exfoliated
Colours	Austral Coffee, Desert Rose, Austral Juperana, Desert Brown, Garnet Ice, Austral Verde & Austral Black
Product Code	
Format	Full Nose Bullnose
Place of Manufacture	-
Length (mm)	-
Width (mm)	-
Height (mm)	-
Size	
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f 'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	No
Declare	Yes
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification

Product Details

Product Range	Commercial Natural Stone
Texture Finish	Polished
Colours	Austral Black, Austral Juperana, Austral Verde, Desert Brown, Desert Rose, Garnet Ice & Austral Coffee
Product Code	
Format	Half Nose Bullnose
Place of Manufacture	-
Length (mm)	-
Width (mm)	-
Height (mm)	-
Size	
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f 'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	No
Declare	Yes
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf 36: 240 minutes. Please note FRL applies up to 3m high - restrained on to

Product Details

Product Range	Commercial Natural Stone
Texture Finish	Exfoliated
Colours	Austral Coffee, Austral Black, Austral Verde, Austral Juperana, Desert Brown, Desert Rose & Garnet Ice
Product Code	
Format	Directional Tactile Paver
Place of Manufacture	-
Length (mm)	-
Width (mm)	-
Height (mm)	-
Size	
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f 'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	No
Declare	Yes
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf 36: 240 minutes. Please note FRL applies up to 3m high - restrained on to

Product Details

Product Range	Commercial Natural Stone
Texture Finish	Honed
Colours	Austral Black, Austral Coffee, Austral Verde, Desert Brown, Desert Rose, Garnet Ice & Austral Juperana
Product Code	
Format	Square Edge Bullnose
Place of Manufacture	-
Length (mm)	-
Width (mm)	-
Height (mm)	-
Size	
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f 'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	No
Declare	Yes
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf 36: 240 minutes. Please note FRL applies up to 3m high - restrained on to

Product Details

Product Range	Commercial Natural Stone
Texture Finish	Polished
Colours	Austral Coffee, Austral Juperana, Desert Brown, Austral Black, Desert Rose, Austral Verde & Garnet Ice
Product Code	
Format	Square Edge Bullnose
Place of Manufacture	-
Length (mm)	-
Width (mm)	-
Height (mm)	-
Size	
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f 'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	No
Declare	Yes
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf 36: 240 minutes. Please note FRL applies up to 3m high - restrained on to

Product Details

Product Range	Commercial Natural Stone
Texture Finish	Exfoliated
Colours	Austral Black, Desert Brown, Austral Coffee, Austral Verde, Garnet Ice, Austral Juperana & Desert Rose
Product Code	
Format	Cobbletop Paver
Place of Manufacture	-
Length (mm)	-
Width (mm)	-
Height (mm)	-
Size	
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f 'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	No
Declare	Yes
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf 36: 240 minutes. Please note FRL applies up to 3m high - restrained on to

Product Details

Product Range	Commercial Natural Stone
Texture Finish	Polished
Colours	Austral Verde, Austral Coffee, Desert Rose, Austral Juperana, Garnet Ice, Austral Black & Desert Brown
Product Code	
Format	Dual Step Tread
Place of Manufacture	-
Length (mm)	-
Width (mm)	-
Height (mm)	-
Size	
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f 'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	No
Declare	Yes
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification

Product Details

Product Range	Commercial Natural Stone
Texture Finish	Exfoliated
Colours	Austral Verde, Austral Black, Desert Brown, Garnet Ice, Austral Coffee, Austral Juperana & Desert Rose
Product Code	
Format	Square Edge Bullnose
Place of Manufacture	-
Length (mm)	-
Width (mm)	-
Height (mm)	-
Size	
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f 'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	No
Declare	Yes
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf 36: 240 minutes. Please note FRL applies up to 3m high - restrained on to

Product Details

Product Range	Commercial Natural Stone
Texture Finish	Exfoliated
Colours	Austral Juperana, Desert Brown, Desert Rose, Austral Verde, Garnet Ice, Austral Coffee & Austral Black
Product Code	
Format	Dual Step Tread
Place of Manufacture	-
Length (mm)	-
Width (mm)	-
Height (mm)	-
Size	
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f 'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	No
Declare	Yes
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification

Product Details

Product Range	Commercial Natural Stone
Texture Finish	Honed
Colours	Austral Coffee, Austral Black, Desert Rose, Desert Brown, Austral Verde, Austral Juperana & Garnet Ice
Product Code	
Format	Single Groove Bullnose
Place of Manufacture	-
Length (mm)	-
Width (mm)	-
Height (mm)	-
Size	
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f 'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	No
Declare	Yes
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf 36: 240 minutes. Please note FRL applies up to 3m high - restrained on to

Product Details

Product Range	Commercial Natural Stone
Texture Finish	Honed
Colours	Garnet Ice, Desert Rose, Austral Verde, Desert Brown, Austral Juperana, Austral Coffee & Austral Black
Product Code	
Format	Triple Groove Bullnose
Place of Manufacture	-
Length (mm)	-
Width (mm)	-
Height (mm)	-
Size	
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f 'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	No
Declare	Yes
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification

Product Details

Product Range	Commercial Natural Stone
Texture Finish	Polished
Colours	Garnet Ice, Desert Brown, Austral Black, Austral Verde, Austral Coffee, Austral Juperana & Desert Rose
Product Code	
Format	Triple Groove Bullnose
Place of Manufacture	-
Length (mm)	-
Width (mm)	-
Height (mm)	-
Size	
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f 'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	No
Declare	Yes
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification

Product Details

Product Range	Commercial Natural Stone
Texture Finish	Honed
Colours	Austral Juperana, Garnet Ice, Desert Brown, Austral Verde, Austral Black, Austral Coffee & Desert Rose
Product Code	
Format	Standard Paver
Place of Manufacture	-
Length (mm)	-
Width (mm)	-
Height (mm)	-
Size	
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f 'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	No
Declare	Yes
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf 36: 240 minutes. Please note FRL applies up to 3m high - restrained on to

Product Details

Product Range	Commercial Natural Stone
Texture Finish	Honed
Colours	Austral Black, Austral Verde, Desert Brown, Garnet Ice, Austral Coffee, Austral Juperana & Desert Rose
Product Code	
Format	Half Nose Bullnose
Place of Manufacture	-
Length (mm)	-
Width (mm)	-
Height (mm)	-
Size	
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f 'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	No
Declare	Yes
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf 36: 240 minutes. Please note FRL applies up to 3m high - restrained on to

Product Details

Product Range	Commercial Natural Stone
Texture Finish	Exfoliated
Colours	Austral Verde, Garnet Ice, Austral Coffee, Austral Black, Desert Brown, Desert Rose & Austral Juperana
Product Code	
Format	Chamfered Edge Bullnose
Place of Manufacture	-
Length (mm)	-
Width (mm)	-
Height (mm)	-
Size	
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f 'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	No
Declare	Yes
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf 36: 240 minutes. Please note FRL applies up to 3m high - restrained on to

Product Details

Product Range	Commercial Natural Stone
Texture Finish	Exfoliated
Colours	Austral Juperana, Desert Brown, Garnet Ice, Austral Black, Austral Verde, Austral Coffee & Desert Rose
Product Code	
Format	Single Groove Bullnose
Place of Manufacture	-
Length (mm)	-
Width (mm)	-
Height (mm)	-
Size	
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f 'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	No
Declare	Yes
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification

Product Details

Product Range	Commercial Natural Stone
Texture Finish	Honed
Colours	Desert Brown, Garnet Ice, Austral Coffee, Austral Black, Austral Verde, Austral Juperana & Desert Rose
Product Code	
Format	Dual Step Tread
Place of Manufacture	-
Length (mm)	-
Width (mm)	-
Height (mm)	-
Size	
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f 'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	No
Declare	Yes
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification

Product Details

Product Range	Commercial Natural Stone
Texture Finish	Polished
Colours	Austral Coffee, Austral Verde, Austral Black, Desert Rose, Desert Brown, Austral Juperana & Garnet Ice
Product Code	
Format	Shark Nose Bullnose
Place of Manufacture	-
Length (mm)	-
Width (mm)	-
Height (mm)	-
Size	
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f 'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	No
Declare	Yes
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf 36: 240 minutes. Please note FRL applies up to 3m high - restrained on to

Product Details

Product Range	Commercial Natural Stone
Texture Finish	Exfoliated
Colours	Austral Verde, Garnet Ice, Austral Coffee, Austral Juperana, Desert Rose, Austral Black & Desert Brown
Product Code	
Format	Triple Groove Bullnose
Place of Manufacture	-
Length (mm)	-
Width (mm)	-
Height (mm)	-
Size	
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f 'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	No
Declare	Yes
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf 36: 240 minutes. Please note FRL applies up to 3m high - restrained on to

Product Details

Product Range	Commercial Natural Stone
Texture Finish	Honed
Colours	Austral Coffee, Desert Brown, Desert Rose, Garnet Ice, Austral Juperana, Austral Verde & Austral Black
Product Code	
Format	Full Nose Bullnose
Place of Manufacture	-
Length (mm)	-
Width (mm)	-
Height (mm)	-
Size	
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f 'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	No
Declare	Yes
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification

Product Details

Product Range	Commercial Natural Stone
Texture Finish	Honed
Colours	Garnet Ice, Austral Juperana, Austral Black, Austral Coffee, Austral Verde, Desert Rose & Desert Brown
Product Code	
Format	Chamfered Edge Bullnose
Place of Manufacture	-
Length (mm)	-
Width (mm)	-
Height (mm)	-
Size	
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f 'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	No
Declare	Yes
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf 36: 240 minutes. Please note FRL applies up to 3m high - restrained on to

Product Details

Product Range	Commercial Natural Stone
Texture Finish	Exfoliated
Colours	Desert Rose, Austral Verde, Desert Brown, Garnet Ice, Austral Juperana, Austral Black & Austral Coffee
Product Code	
Format	Standard Paver
Place of Manufacture	-
Length (mm)	-
Width (mm)	-
Height (mm)	-
Size	
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f 'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	No
Declare	Yes
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf 36: 240 minutes. Please note FRL applies up to 3m high - restrained on to

Product Details

Product Range	Commercial Natural Stone
Texture Finish	Polished
Colours	Austral Verde, Austral Black, Austral Juperana, Austral Coffee, Garnet Ice, Desert Brown & Desert Rose
Product Code	
Format	Standard Paver
Place of Manufacture	-
Length (mm)	-
Width (mm)	-
Height (mm)	-
Size	
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f 'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	No
Declare	Yes
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf 36: 240 minutes. Please note FRL applies up to 3m high - restrained on to

Product Details

Product Range	Commercial Natural Stone
Texture Finish	Honed
Colours	Austral Black, Austral Verde, Austral Juperana, Garnet Ice, Desert Rose, Austral Coffee & Desert Brown
Product Code	
Format	Shark Nose Bullnose
Place of Manufacture	-
Length (mm)	-
Width (mm)	-
Height (mm)	-
Size	
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f 'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	No
Declare	Yes
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification

Product Details

Product Range	Commercial Natural Stone
Texture Finish	Polished
Colours	Garnet Ice, Desert Rose, Desert Brown, Austral Juperana, Austral Black, Austral Verde & Austral Coffee
Product Code	
Format	Chamfered Edge Bullnose
Place of Manufacture	-
Length (mm)	-
Width (mm)	-
Height (mm)	-
Size	
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f 'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	No
Declare	Yes
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf 36: 240 minutes. Please note FRL applies up to 3m high - restrained on to

Product Details

Product Range	Commercial Natural Stone
Texture Finish	Exfoliated
Colours	Desert Brown, Austral Juperana, Desert Rose, Austral Verde, Austral Black, Garnet Ice & Austral Coffee
Product Code	
Format	Hazard Tactile Paver
Place of Manufacture	-
Length (mm)	-
Width (mm)	-
Height (mm)	-
Size	
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f 'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	No
Declare	Yes
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf 36: 240 minutes. Please note FRL applies up to 3m high - restrained on to

Product Details

Product Range	Commercial Natural Stone
Texture Finish	Exfoliated
Colours	Desert Brown, Austral Juperana, Garnet Ice, Desert Rose, Austral Black, Austral Coffee & Austral Verde
Product Code	
Format	Half Nose Bullnose
Place of Manufacture	-
Length (mm)	-
Width (mm)	-
Height (mm)	-
Size	
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f 'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	-
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	No
Declare	Yes
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf 36: 240 minutes. Please note FRL applies up to 3m high - restrained on to