

GB Vertico Smooth Range Technical Data Sheet



Product Range	Product Name	Dimension Illustration	Swatch	State	Length (mm)	Width (mm)	Height (mm)	Average Weight / Unit (kg)	Pack Size	Characteristic Unconfined Compressive Strength (f _{uc}) MPa	Durability Class
GB Vertico Smooth	Limestone 20.01 Standard Block 390x190x190			WA	390	190	190	15.6			Exposure Grade
GB Vertico Smooth	Porcelain 20.21 Corner Block 390x190x190			WA	390	190	190	15.6			Exposure Grade
GB Vertico Smooth	Porcelain 20.42 Channel 390x190x190			WA	390	190	190	15.6			Exposure Grade
GB Vertico Smooth	Pewter 20.21 Corner Block 390x190x190			WA	390	190	190	15.6			Exposure Grade
GB Vertico Smooth	Limestone 20.21 Corner Block 390x190x190			WA	390	190	190	15.6			Exposure Grade
GB Vertico Smooth	Pottery 20.01 Standard Block 390x190x190			WA	390	190	190				Exposure Grade
GB Vertico Smooth	Pewter 20.42 Channel 390x190x190			WA	390	190	190	15.6			Exposure Grade
GB Vertico Smooth	Nickel 20.01 Standard Block 390x190x190			WA	390	190	190	15.6			Exposure Grade
GB Vertico Smooth	Pottery 20.42 Channel 390x190x190			WA	390	190	190				Exposure Grade
GB Vertico Smooth	Pebble 20.01 Standard Block 390x190x190			WA	390	190	190	15.6			Exposure Grade
GB Vertico Smooth	Pebble 20.42 Channel 390x190x190			WA	390	190	190	15.6			Exposure Grade
GB Vertico Smooth	Limestone 20.42 Channel 390x190x190			WA	390	190	190	15.6			Exposure Grade
GB Vertico Smooth	Porcelain 20.01 Standard Block 390x190x190			WA	390	190	190	15.6			Exposure Grade
GB Vertico Smooth	Pebble 20.21 Corner Block 390x190x190			WA	390	190	190	15.6			Exposure Grade
GB Vertico Smooth	Pottery 20.21 Corner Block 390x190x190 - G2021RBPT-1		PREVIEW NOT AVAILABLE	WA	390	190	190	15.6	90	>15	Exposure Grade
GB Vertico Smooth	Nickel 20.42 Channel 390x190x190			WA	390	190	190	15.6			Exposure Grade
GB Vertico Smooth	Nickel 20.21 Corner Block 390x190x190			WA	390	190	190	15.6			Exposure Grade



This Data represents average results from commercial production lots.

If specific test results are required, sample should be taken from current production lots.

AUSTRALIAN STANDARD TEST METHODS AS/NSZ 4456 ARE USED AS APPLICABLE.

Please note: FRL applies up to 3m high - restrained on top and bottom.



Product Range	Product Name	Dimension Illustration	Swatch	State	Length (mm)	Width (mm)	Height (mm)	Average Weight /Unit (kg)	Pack Size	Characteristic Unconfined Compressive Strength (f _{uc}) MPa	Durability Class
GB Vertico Smooth	Pewter 20.01 Standard Block 390x190x190			WA	390	190	190	15.6			Exposure Grade

This Data represents average results from commercial production lots.

If specific test results are required, sample should be taken from current production lots.

AUSTRALIAN STANDARD TEST METHODS AS/NSZ 4456 ARE USED AS APPLICABLE.

Please note: FRL applies up to 3m high - restrained on top and bottom.

