



Industrial WA Range Technical Data Sheet

BRICKWORKS

Product Range	Product Name	Dimension Illustration	Swatch	State	Length (mm)	Width (mm)	Height (mm)	Dimensional Category	Core Volume (%)	Units per Square Metre	Pack Size	Characteristic Unconfined Compressive Strength (f _{uc}) MPa	Maximum Cold Water Absorption (%)	Initial Rate of Absorption (IRA) (kg/m ² min)	Coefficient of Expansion e Factor (mm/m)	Durability Class	Liability to Efflorescence	Lime Pitting Liability
Industrial WA	Industrial Foundry			WA	290	90	76									Exposure Grade		
Industrial WA	Industrial Char			WA	230	110	76	DW2	<30	48.5	264	>12	<9	<1.5	<0.9	Exposure Grade	Slight	Nil
Industrial WA	Industrial Foundry			WA	230	110	76	DW2	<30	48.5	264	>12	<9	<1.5	<0.9	Exposure Grade	Slight	Nil

This Data represents average results from commercial production lots.

If specific test results are required, sample should be taken from current production lots.

AUSTRALIAN STANDARD TEST METHODS AS/NSZ 4456 ARE USED AS APPLICABLE.

Please note: FRL applies up to 3m high - restrained on top and bottom.