

































# GB Sandstone Rock Face Range Technical Data Sheet

Product Range	Product Name	Dimension Illustration	Swatch	State	Length (mm)	Width (mm)	Height (mm)	Average Weight / Unit (kg)	Characteristic Unconfined Compressive Strength (f <sub>uc</sub> ) MPa	Durability Class
GB Sandstone Rock Face	Limestone 20.127 HS Half Height 390x190x90			WA	390	190	90	8.3		Exposure Grade
GB Sandstone Rock Face	Brisbane Blend 10.125 HS Corner Return 390x190x190			WA	390	190	190	20		Exposure Grade
GB Sandstone Rock Face	Brisbane Blend 10.93 HS Half 190x90x190			WA	190	90	190	5.4		Exposure Grade
GB Sandstone Rock Face	Sydney Blend 20.142 Channel 390x190x190			WA	390	190	190	17.25		Exposure Grade
GB Sandstone Rock Face	Brisbane Blend 50.39 Corner Capping Tile 390x190x65			WA	390	190	65	13.2	>15	Exposure Grade
GB Sandstone Rock Face	Endeavour Blend 20.142 Channel 390x190x190			WA	390	190	190	17.25		Exposure Grade
GB Sandstone Rock Face	Sydney Blend 10.92 HS Three Quarter 290x90x190			WA	290	90	190	9.1		Exposure Grade
GB Sandstone Rock Face	Limestone 50.39 Corner Capping Tile 390x190x65			WA	390	190	65	13.2	>15	Exposure Grade
GB Sandstone Rock Face	Endeavour Blend 10.125 HS Corner Return 390x190x190			WA	390	190	190	20		Exposure Grade
GB Sandstone Rock Face	Limestone 20.145 Cleanout 390x190x190			WA	390	190	190	16.7		Exposure Grade
GB Sandstone Rock Face	Sydney Blend 50.65 Split Pier Capping Tile 325x325x65			WA	325	325	65	13.2		Exposure Grade
GB Sandstone Rock Face	Limestone 10.93 HS Half 190x90x190			WA	190	90	190	5.4		Exposure Grade
GB Sandstone Rock Face	Sydney Blend 20.145 Cleanout 390x190x190			WA	390	190	190	16.7		Exposure Grade
GB Sandstone Rock Face	Sydney Blend 20.127 HS Half Height 390x190x90			WA	390	190	90	8.3		Exposure Grade
GB Sandstone Rock Face	Endeavour Blend 10.92 HS Three Quarter 290x90x190			WA	290	90	190	9.1		Exposure Grade
GB Sandstone Rock Face	Brisbane Blend 20.123 Half 190x190x190			WA	190	190	190	9.5		Exposure Grade
GB Sandstone Rock Face	Sydney Blend 10.95 HS Veneer Solid 390x90x190			WA	390	90	190	14.5		Exposure Grade




































This Data represents average results from commercial production lots.

If specific test results are required, sample should be taken from current production lots.

AUSTRALIAN STANDARD TEST METHODS AS/NZS 4456 ARE USED AS APPLICABLE.

Please note: FRL applies up to 3m high - restrained on top and bottom.




Product Range	Product Name	Dimension Illustration	Swatch	State	Length (mm)	Width (mm)	Height (mm)	Average Weight /Unit (kg)	Characteristic Unconfined Compressive Strength (f <sub>uc</sub> ) MPa	Durability Class
GB Sandstone Rock Face	Sydney Blend 50.39 Corner Capping Tile 390x190x65			WA	390	190	65	13.2	>15	Exposure Grade
GB Sandstone Rock Face	Sydney Blend 20.139 HS Corner 390x190x190			WA	390	190	190	18.2		Exposure Grade
GB Sandstone Rock Face	Brisbane Blend 20.133 HS Knockout 390x190x190			WA	390	190	190	16.7		Exposure Grade
GB Sandstone Rock Face	Limestone 10.92 HS Three Quarter 290x90x190			WA	290	90	190	9.1		Exposure Grade
GB Sandstone Rock Face	Brisbane Blend 10.92 HS Three Quarter 290x90x190			WA	290	90	190	9.1		Exposure Grade
GB Sandstone Rock Face	Brisbane Blend 20.121 Standard 390x190x190			WA	390	190	190	17.3		Exposure Grade
GB Sandstone Rock Face	Brisbane Blend 20.139 HS Corner 390x190x190			WA	390	190	190	18.2		Exposure Grade
GB Sandstone Rock Face	Endeavour Blend 20.133 HS Knockout 390x190x190			WA	390	190	190	16.7		Exposure Grade
GB Sandstone Rock Face	Endeavour Blend 20.145 Cleanout 390x190x190			WA	390	190	190	16.7		Exposure Grade
GB Sandstone Rock Face	Sydney Blend 20.133 HS Knockout 390x190x190			WA	390	190	190	16.7		Exposure Grade
GB Sandstone Rock Face	Limestone 20.123 Half 190x190x190			WA	190	190	190	9.5		Exposure Grade
GB Sandstone Rock Face	Limestone 10.95 HS Veneer Solid 390x90x190			WA	390	90	190	14.5		Exposure Grade
GB Sandstone Rock Face	Endeavour Blend 10.95 HS Veneer Solid 390x90x190			WA	390	90	190	14.5		Exposure Grade
GB Sandstone Rock Face	Brisbane Blend 50.70 Split Step Tread 390x350x65			WA	390	350	65	16.9		Exposure Grade
GB Sandstone Rock Face	Limestone 20.142 Channel 390x190x190			WA	390	190	190	17.25		Exposure Grade
GB Sandstone Rock Face	Endeavour Blend 50.65 Split Pier Capping Tile 325x325x65			WA	325	325	65	13.2		Exposure Grade
GB Sandstone Rock Face	Endeavour Blend 20.123 Half 190x190x190			WA	190	190	190	9.5		Exposure Grade
GB Sandstone Rock Face	Brisbane Blend 20.127 HS Half Height 390x190x90			WA	390	190	90	8.3		Exposure Grade

This Data represents average results from commercial production lots.

If specific test results are required, sample should be taken from current production lots.

AUSTRALIAN STANDARD TEST METHODS AS/NSZ 4456 ARE USED AS APPLICABLE.

Please note: FRL applies up to 3m high - restrained on top and bottom.




Product Range	Product Name	Dimension Illustration	Swatch	State	Length (mm)	Width (mm)	Height (mm)	Average Weight /Unit (kg)	Characteristic Unconfined Compressive Strength (f <sub>uc</sub> ) MPa	Durability Class
GB Sandstone Rock Face	Sydney Blend 10.93 HS Half 190x90x190			WA	190	90	190	5.4		Exposure Grade
GB Sandstone Rock Face	Brisbane Blend 50.66 4 Sided Capping Tile 330x330x65			WA	330	330	65			Exposure Grade
GB Sandstone Rock Face	Sydney Blend 20.121 Standard 390x190x190			WA	390	190	190	17.3		Exposure Grade
GB Sandstone Rock Face	Endeavour Blend 20.121 Standard 390x190x190			WA	390	190	190	17.3		Exposure Grade
GB Sandstone Rock Face	Limestone 20.139 HS Corner 390x190x190			WA	390	190	190	18.2		Exposure Grade
GB Sandstone Rock Face	Brisbane Blend 20.145 Cleanout 390x190x190			WA	390	190	190	16.7		Exposure Grade
GB Sandstone Rock Face	Endeavour Blend 20.139 HS Corner 390x190x190			WA	390	190	190	18.2		Exposure Grade
GB Sandstone Rock Face	Sydney Blend 10.125 HS Corner Return 390x190x190			WA	390	190	190	20		Exposure Grade
GB Sandstone Rock Face	Brisbane Blend 10.95 HS Veneer Solid 390x90x190			WA	390	90	190	14.5		Exposure Grade
GB Sandstone Rock Face	Limestone 50.70 Split Step Tread 390x350x65			WA	390	350	65	16.9		Exposure Grade
GB Sandstone Rock Face	Brisbane Blend 50.65 Split Pier Capping Tile 325x325x65			WA	325	325	65	13.2		Exposure Grade
GB Sandstone Rock Face	Endeavour Blend 50.70 Split Step Tread 390x350x65			WA	390	350	65	16.9		Exposure Grade
GB Sandstone Rock Face	Endeavour Blend 50.39 Corner Capping Tile 390x190x65			WA	390	190	65	13.2	>15	Exposure Grade
GB Sandstone Rock Face	Limestone 10.125 HS Corner Return 390x190x190			WA	390	190	190	20		Exposure Grade
GB Sandstone Rock Face	Limestone 20.121 Standard 390x190x190			WA	390	190	190	17.3		Exposure Grade
GB Sandstone Rock Face	Endeavour Blend 10.93 HS Half 190x90x190			WA	190	90	190	5.4		Exposure Grade
GB Sandstone Rock Face	Brisbane Blend 20.142 Channel 390x190x190			WA	390	190	190	17.25		Exposure Grade
GB Sandstone Rock Face	Sydney Blend 20.123 Half 190x190x190			WA	190	190	190	9.5		Exposure Grade











This Data represents average results from commercial production lots.

If specific test results are required, sample should be taken from current production lots.

AUSTRALIAN STANDARD TEST METHODS AS/NZS 4456 ARE USED AS APPLICABLE.

Please note: FRL applies up to 3m high - restrained on top and bottom.



Product Range	Product Name	Dimension Illustration	Swatch	State	Length (mm)	Width (mm)	Height (mm)	Average Weight /Unit (kg)	Characteristic Unconfined Compressive Strength (f <sub>uc</sub> ) MPa	Durability Class
GB Sandstone Rock Face	Limestone 20.133 HS Knockout 390x190x190			WA	390	190	190	16.7		Exposure Grade
GB Sandstone Rock Face	Sydney Blend 50.70 Split Step Tread 390x350x65			WA	390	350	65	16.9		Exposure Grade
GB Sandstone Rock Face	Sydney Blend 50.66 4 Sided Capping Tile 330x330x65			WA	330	330	65			Exposure Grade
GB Sandstone Rock Face	Endeavour Blend 20.127 HS Half Height 390x190x90			WA	390	190	90	8.3		Exposure Grade
GB Sandstone Rock Face	Limestone 50.65 Split Pier Capping Tile 325x325x65			WA	325	325	65	13.2		Exposure Grade

This Data represents average results from commercial production lots.

If specific test results are required, sample should be taken from current production lots.

AUSTRALIAN STANDARD TEST METHODS AS/NSZ 4456 ARE USED AS APPLICABLE.

Please note: FRL applies up to 3m high - restrained on top and bottom.

