

# GB Smooth Range Technical Data Sheet

# BRICKWORKS

Product Range	Product Name	Dimension Illustration	Swatch	State	Length (mm)	Width (mm)	Height (mm)	Average Weight / Unit (kg)	Core Volume (%)	Units per Square Metre	Pack Size	Characteristic Unconfined Compressive Strength (f <sub>uc</sub> ) MPa	Durability Class	LRV
GB Smooth	Pottery 20.03B Half Bullnose 190x190x190			WA	190	190	190	8.7	47	25	180		Exposure Grade	
GB Smooth	Pebble 50.31 Capping Unit 390x190x40			WA	390	190	40	6.1					Exposure Grade	
GB Smooth	Limestone 20.13 Half Lintel 190x190x190			WA	190	190	190	8.7					Exposure Grade	
GB Smooth	Pottery 20.38 Half Height Sill 245x190x90			WA	245	190	90						Exposure Grade	
GB Smooth	Pottery 20.13 Half Lintel 190x190x190			WA	190	190	190						Exposure Grade	
GB Smooth	Nickel 20.03B Half Bullnose 190x190x190			WA	190	190	190	8.7	47	25	180		Exposure Grade	
GB Smooth	Porcelain 10.25 Corner Return 390x90x190			WA	390	90	190	13.3					Exposure Grade	
GB Smooth	Porcelain 20.42 Channel 390x190x190			WA	390	190	190	15.625					Exposure Grade	
GB Smooth	Nickel 20.01B Standard Bullnose 390x190x190			WA	390	190	190	15.6	47	12.5	180	>15	Exposure Grade	
GB Smooth	Porcelain 20.01 Standard 390x190x190			WA	390	190	190	15.625					Exposure Grade	
GB Smooth	Limestone 20.01 Standard 390x190x190			WA	390	190	190	15.2					Exposure Grade	
GB Smooth	Porcelain 30.42 Channel 390x290x190			WA	390	290	190	20			180	>15	Exposure Grade	57.9
GB Smooth	Limestone 30.42 Channel 390x290x190			WA	390	290	190	20			180	>15	Exposure Grade	51.8
GB Smooth	Porcelain 10.03 Half 190x90x190			WA	190	90	190	4.9					Exposure Grade	
GB Smooth	Pewter 30.02 Three Quarter 290x290x190			WA	290	290	190	16.7					Exposure Grade	
GB Smooth	Pewter 20.73 Half Height Half 190x190x90			WA	190	190	90	4					Exposure Grade	
GB Smooth	Limestone 20.20 Knockout 390x190x190			WA	390	190	190	15.2					Exposure Grade	

This Data represents average results from commercial production lots.

If specific test results are required, sample should be taken from current production lots.

AUSTRALIAN STANDARD TEST METHODS AS/NZS 4456 ARE USED AS APPLICABLE.

Please note: FRL applies up to 3m high - restrained on top and bottom.



Product Range	Product Name	Dimension Illustration	Swatch	State	Length (mm)	Width (mm)	Height (mm)	Average Weight /Unit (kg)	Core Volume (%)	Units per Square Metre	Pack Size	Characteristic Unconfined Compressive Strength (f'uc) MPa	Durability Class	LRV
GB Smooth	Pebble 30.01 Standard 390x290x190			WA	390	290	190	20					Exposure Grade	
GB Smooth	Limestone 20.71 Half Height 390x190x90			WA	390	190	90	8					Exposure Grade	
GB Smooth	Limestone 10.03 Half 190x90x190			WA	190	90	190	4.9					Exposure Grade	
GB Smooth	Pewter 10.725 Half Height Corner10.725 Half Height Corner 390x190x90			WA	390	190	90	6.7					Exposure Grade	
GB Smooth	Nickel 20.03 Half 190x190x190			WA	190	190	190	8.7					Exposure Grade	
GB Smooth	Porcelain 10.725 Half Height Corner10.725 Half Height Corner 390x190x90			WA	390	190	90	6.7					Exposure Grade	
GB Smooth	Pewter 20.13 Half Lintel 190x190x190			WA	190	190	190	8.7					Exposure Grade	
GB Smooth	Limestone 50.31 Capping Unit 390x190x40			WA	390	190	40	6.1					Exposure Grade	
GB Smooth	Nickel 10.71 Standard Half Height 390x90x90			WA	390	90	90	5.3					Exposure Grade	
GB Smooth	Nickel 20.01 Standard 390x190x190			WA	390	190	190	15.625					Exposure Grade	
GB Smooth	Nickel 10.25 Corner Return 390x90x190			WA	390	90	190	13.3					Exposure Grade	
GB Smooth	Nickel 20.45 Cleanout Block 390x190x190			WA	390	190	190	15.625					Exposure Grade	
GB Smooth	Pebble 30.02 Three Quarter 290x290x190			WA	290	290	190	16.7					Exposure Grade	
GB Smooth	Nickel 20.13 Half Lintel 190x190x190			WA	190	190	190	8.7					Exposure Grade	
GB Smooth	Limestone 20.03 Half 190x190x190			WA	190	190	190	8.7					Exposure Grade	
GB Smooth	Pottery 20.42 Channel 390x190x190			WA	390	190	190						Exposure Grade	
GB Smooth	Pebble 30.42 Channel 390x290x190			WA	390	290	190	20			180	>15	Exposure Grade	34
GB Smooth	Pebble 10.25 Corner Return 390x90x190			WA	390	90	190	13.3					Exposure Grade	

This Data represents average results from commercial production lots.

If specific test results are required, sample should be taken from current production lots.

AUSTRALIAN STANDARD TEST METHODS AS/NSZ 4456 ARE USED AS APPLICABLE.

Please note: FRL applies up to 3m high - restrained on top and bottom.




Product Range	Product Name	Dimension Illustration	Swatch	State	Length (mm)	Width (mm)	Height (mm)	Average Weight /Unit (kg)	Core Volume (%)	Units per Square Metre	Pack Size	Characteristic Unconfined Compressive Strength (f'uc) MPa	Durability Class	LRV
GB Smooth	Pebble 20.01B Standard Bullnose 390x190x190			WA	390	190	190	15.6	47	12.5	180	>15	Exposure Grade	
GB Smooth	Pewter 20.03B Half Bullnose 190x190x190			WA	190	190	190	8.7	47	25	180		Exposure Grade	
GB Smooth	Limestone 30.01 Standard 390x290x190			WA	390	290	190	20					Exposure Grade	
GB Smooth	Limestone 10.01 Standard 390x90x190			WA	390	90	190	10					Exposure Grade	
GB Smooth	Porcelain 20.01B Standard Bullnose 390x190x190			WA	390	190	190	15.6	47	12.5	180	>15	Exposure Grade	
GB Smooth	Pebble 10.01 Standard 390x90x190			WA	390	90	190	10					Exposure Grade	
GB Smooth	Porcelain 10.71 Standard Half Height 390x90x90			WA	390	90	90	5.3					Exposure Grade	
GB Smooth	Limestone 10.25 Corner Return 390x90x190			WA	390	90	190	13.3					Exposure Grade	
GB Smooth	Pewter 10.01 Standard 390x90x190			WA	390	90	190	10					Exposure Grade	
GB Smooth	Porcelain 20.03B Half Bullnose 190x190x190			WA	190	190	190	8.7	47	25	180		Exposure Grade	
GB Smooth	Pebble 20.42 Channel 390x190x190			WA	390	190	190	15.625					Exposure Grade	
GB Smooth	Pottery 20.73 Half Height Half 190x190x90			WA	190	190	90						Exposure Grade	
GB Smooth	Limestone 20.38 Half Height Sill 130x190x90			WA	130	190	90	8.3					Exposure Grade	
GB Smooth	Porcelain 20.03 Half 190x190x190			WA	190	190	190	8.7					Exposure Grade	
GB Smooth	Pewter 20.03 Half 190x190x190			WA	190	190	190	8.7					Exposure Grade	
GB Smooth	Nickel 10.725 Half Height Corner 10.725 Half Height Corner 390x190x90			WA	390	190	90	6.7					Exposure Grade	
GB Smooth	Porcelain 50.31 Capping Unit 390x190x40			WA	390	190	40	6.1					Exposure Grade	
GB Smooth	Pewter 20.71 Half Height 390x190x90			WA	390	190	90	8					Exposure Grade	

This Data represents average results from commercial production lots.

If specific test results are required, sample should be taken from current production lots.

AUSTRALIAN STANDARD TEST METHODS AS/NZS 4456 ARE USED AS APPLICABLE.

Please note: FRL applies up to 3m high - restrained on top and bottom.



Product Range	Product Name	Dimension Illustration	Swatch	State	Length (mm)	Width (mm)	Height (mm)	Average Weight /Unit (kg)	Core Volume (%)	Units per Square Metre	Pack Size	Characteristic Unconfined Compressive Strength (f'uc) MPa	Durability Class	LRV
GB Smooth	Pebble 10.725 Half Height Corner 10.725 Half Height Corner 390x190x90			WA	390	190	90	6.7					Exposure Grade	
GB Smooth	Limestone 30.02 Three Quarter 290x290x190			WA	290	290	190	16.7					Exposure Grade	
GB Smooth	Pottery 10.71 Standard Half Height 390x90x90			WA	390	90	90						Exposure Grade	
GB Smooth	Pottery 20.03 Half 190x190x190			WA	190	190	190						Exposure Grade	
GB Smooth	Pebble 20.03B Half Bullnose 190x190x190			WA	190	190	190	8.7	47	25	180		Exposure Grade	
GB Smooth	Pottery 50.31 Capping Unit 390x190x40			WA	390	190	40						Exposure Grade	
GB Smooth	Limestone 20.45 Cleanout Block 390x190x190			WA	390	190	190	15.2					Exposure Grade	
GB Smooth	Pebble 20.01 Standard 390x190x190			WA	390	190	190	15.625					Exposure Grade	
GB Smooth	Pebble 20.03 Half 190x190x190			WA	190	190	190	8.7					Exposure Grade	
GB Smooth	Pewter 20.01 Standard 390x190x190			WA	390	190	190	15.625					Exposure Grade	
GB Smooth	Porcelain 20.20 Knockout 390x190x190			WA	390	190	190	15.2					Exposure Grade	
GB Smooth	Nickel 50.31 Capping Unit 390x190x40			WA	390	190	40	6.1					Exposure Grade	
GB Smooth	Pewter 20.45 Cleanout Block 390x190x190			WA	390	190	190	15.625					Exposure Grade	
GB Smooth	Limestone 20.42 Channel 390x190x190			WA	390	190	190	15.625					Exposure Grade	
GB Smooth	Pebble 10.71 Standard Half Height 390x90x90			WA	390	90	90	5.3					Exposure Grade	
GB Smooth	Limestone 20.73 Half Height Half 190x190x90			WA	190	190	90	4					Exposure Grade	
GB Smooth	Pewter 30.01 Standard 390x290x190			WA	390	290	190	20					Exposure Grade	
GB Smooth	Pewter 20.20 Knockout 390x190x190			WA	390	190	190	15.2					Exposure Grade	

This Data represents average results from commercial production lots.

If specific test results are required, sample should be taken from current production lots.

AUSTRALIAN STANDARD TEST METHODS AS/NZS 4456 ARE USED AS APPLICABLE.

Please note: FRL applies up to 3m high - restrained on top and bottom.




Product Range	Product Name	Dimension Illustration	Swatch	State	Length (mm)	Width (mm)	Height (mm)	Average Weight /Unit (kg)	Core Volume (%)	Units per Square Metre	Pack Size	Characteristic Unconfined Compressive Strength (f'uc) MPa	Durability Class	LRV
GB Smooth	Pewter 50.31 Capping Unit 390x190x40			WA	390	190	40	6.1					Exposure Grade	
GB Smooth	Nickel 10.01 Standard 390x90x190			WA	390	90	190	10					Exposure Grade	
GB Smooth	Pebble 20.20 Knockout 390x190x190			WA	390	190	190	15.2					Exposure Grade	
GB Smooth	Pottery 20.01B Standard Bullnose 390x190x190			WA	390	190	190	15.6	47	12.5	180	>15	Exposure Grade	
GB Smooth	Pottery 20.71 Half Height 390x190x90			WA	390	190	90						Exposure Grade	
GB Smooth	Nickel 20.42 Channel 390x190x190			WA	390	190	190	15.625					Exposure Grade	
GB Smooth	Porcelain 20.73 Half Height Half 190x190x90			WA	190	190	90	4					Exposure Grade	
GB Smooth	Porcelain 20.13 Half Lintel 190x190x190			WA	190	190	190	8.7					Exposure Grade	
GB Smooth	Pewter 30.42 Channel 390x290x190			WA	390	290	190	20			180	>15	Exposure Grade	19.7
GB Smooth	Pebble 20.38 Half Height Sill 130x190x90			WA	130	190	90	8.3					Exposure Grade	
GB Smooth	Porcelain 10.01 Standard 390x90x190			WA	390	90	190	10					Exposure Grade	
GB Smooth	Limestone 20.01B Standard Bullnose 390x190x190			WA	390	190	190	15.6	47	12.5	180	>15	Exposure Grade	
GB Smooth	Nickel 20.73 Half Height Half 190x190x90			WA	190	190	90	4					Exposure Grade	
GB Smooth	Nickel 30.01 Standard 390x290x190			WA	390	290	190	20					Exposure Grade	
GB Smooth	Pebble 10.03 Half 190x90x190			WA	190	90	190	4.9					Exposure Grade	
GB Smooth	Pebble 20.45 Cleanout Block 390x190x190			WA	390	190	190	15.625					Exposure Grade	
GB Smooth	Nickel 20.38 Half Height Sill 130x190x90			WA	130	190	90	8.3					Exposure Grade	
GB Smooth	Limestone 10.725 Half Height Corner 10.725 Half Height Corner 390x190x90			WA	390	190	90	6.7					Exposure Grade	





































This Data represents average results from commercial production lots.

If specific test results are required, sample should be taken from current production lots.

AUSTRALIAN STANDARD TEST METHODS AS/NSZ 4456 ARE USED AS APPLICABLE.

Please note: FRL applies up to 3m high - restrained on top and bottom.



Product Range	Product Name	Dimension Illustration	Swatch	State	Length (mm)	Width (mm)	Height (mm)	Average Weight /Unit (kg)	Core Volume (%)	Units per Square Metre	Pack Size	Characteristic Unconfined Compressive Strength (f'uc) MPa	Durability Class	LRV
GB Smooth	Porcelain 30.02 Three Quarter 290x290x190			WA	290	290	190	16.7					Exposure Grade	
GB Smooth	Pewter 20.01B Standard Bullnose 390x190x190			WA	390	190	190	15.6	47	12.5	180	>15	Exposure Grade	
GB Smooth	Porcelain 20.71 Half Height 390x190x90			WA	390	190	90	8					Exposure Grade	
GB Smooth	Limestone 20.03B Half Bullnose 190x190x190			WA	190	190	190	8.7	47	25	180		Exposure Grade	
GB Smooth	Porcelain 30.01 Standard 390x290x190			WA	390	290	190	20					Exposure Grade	
GB Smooth	Pottery 20.01 Standard 390x190x190			WA	390	190	190						Exposure Grade	
GB Smooth	Nickel 30.42 Channel 390x290x190			WA	390	290	190	20			180	>15	Exposure Grade	30.3
GB Smooth	Pewter 20.42 Channel 390x190x190			WA	390	190	190	15.625					Exposure Grade	
GB Smooth	Pewter 20.38 Half Height Sill 130x190x90			WA	130	190	90	8.3					Exposure Grade	
GB Smooth	Pewter 10.03 Half 190x90x190			WA	190	90	190	4.9					Exposure Grade	
GB Smooth	Nickel 30.02 Three Quarter 290x290x190			WA	290	290	190	16.7					Exposure Grade	
GB Smooth	Limestone 10.71 Standard Half Height 390x90x90			WA	390	90	90	5.3					Exposure Grade	
GB Smooth	Pottery 30.01 Standard 390x290x190			WA	390	290	190						Exposure Grade	
GB Smooth	Porcelain 20.38 Half Height Sill 245X190X90			WA	245	190	90	8.3					Exposure Grade	
GB Smooth	Pebble 20.71 Half Height 390x190x90			WA	390	190	90	8					Exposure Grade	
GB Smooth	Pewter 10.25 Corner Return 390x90x190			WA	390	90	190	13.3					Exposure Grade	
GB Smooth	Nickel 20.71 Half Height 390x190x90			WA	390	190	90	8					Exposure Grade	
GB Smooth	Pebble 20.13 Half Lintel 190x190x190			WA	190	190	190	8.7					Exposure Grade	



This Data represents average results from commercial production lots.

If specific test results are required, sample should be taken from current production lots.

AUSTRALIAN STANDARD TEST METHODS AS/NSZ 4456 ARE USED AS APPLICABLE.

Please note: FRL applies up to 3m high - restrained on top and bottom.



Product Range	Product Name	Dimension Illustration	Swatch	State	Length (mm)	Width (mm)	Height (mm)	Average Weight /Unit (kg)	Core Volume (%)	Units per Square Metre	Pack Size	Characteristic Unconfined Compressive Strength (f'uc) MPa	Durability Class	LRV
GB Smooth	Pewter 10.71 Standard Half Height 390x90x90			WA	390	90	90	5.3					Exposure Grade	
GB Smooth	Porcelain 20.45 Cleanout Block 390x190x190			WA	390	190	190	15.625					Exposure Grade	
GB Smooth	Nickel 10.03 Half 190x90x190			WA	190	90	190	4.9					Exposure Grade	
GB Smooth	Nickel 20.20 Knockout 390x190x190			WA	390	190	190	15.2					Exposure Grade	

This Data represents average results from commercial production lots.

If specific test results are required, sample should be taken from current production lots.

AUSTRALIAN STANDARD TEST METHODS AS/NSZ 4456 ARE USED AS APPLICABLE.

Please note: FRL applies up to 3m high - restrained on top and bottom.

