


Product Details

Product Range	GB Vertico Smooth
Texture Finish	Smooth
Colours	Limestone, Pottery, Nickel, Pebble, Porcelain & Pewter
Product Code	
Format	20.01 Standard Block
Place of Manufacture	Gympie, Queensland
Length (mm)	390
Width (mm)	190
Height (mm)	190
Size	390x190x190
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f'uc) MPa	-
Minimum Shell Thickness (mm)	30
Weight	15.6
Units Per Tonne	64.1
Units Per Pallet	90
Units per Square Metre	-
Durability Class	Exposure Grade
Slip Resistance	
Wall Mass Inc Hollow	199
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	Yes
Declare	No
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	60 to 240 (see notes)
Integrity	60
Insulation	60


Notes

Maximum slenderness ratio (srf) unreinforced masonry from AS3700:2018 Table 6.1 is: 18.0 at 60 minutes | 17.0 at 90 minutes | 16.0 at 120 minutes | 15.5 at 180 minutes | 15.5 at 240 minutes. This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf 36: 240 minutes

Product Details

Product Range	GB Vertico Smooth
Texture Finish	Smooth
Colours	Porcelain, Pewter, Limestone, Pebble, Pottery & Nickel
Product Code	
Format	20.21 Corner Block
Place of Manufacture	Gympie, Queensland
Length (mm)	390
Width (mm)	190
Height (mm)	190
Size	390x190x190
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f'uc) MPa	-
Minimum Shell Thickness (mm)	30
Weight	15.6
Units Per Tonne	64.1
Units Per Pallet	90
Units per Square Metre	-
Durability Class	Exposure Grade
Slip Resistance	
Wall Mass Inc Hollow	199
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	Yes
Declare	No
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	60 to 240 (see notes)
Integrity	60
Insulation	60


Notes

Maximum slenderness ratio (srf) unreinforced masonry from AS3700:2018 Table 6.1 is: 18.0 at 60 minutes | 17.0 at 90 minutes | 16.0 at 120 minutes | 15.5 at 180 minutes | 15.5 at 240 minutes. This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf 36: 240 minutes

Product Details

Product Range	GB Vertico Smooth
Texture Finish	Smooth
Colours	Porcelain, Pewter, Pottery, Pebble, Limestone & Nickel
Product Code	
Format	20.42 Channel
Place of Manufacture	Gympie, Queensland
Length (mm)	390
Width (mm)	190
Height (mm)	190
Size	390x190x190
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f'uc) MPa	-
Minimum Shell Thickness (mm)	30
Weight	15.6
Units Per Tonne	64.1
Units Per Pallet	90
Units per Square Metre	-
Durability Class	Exposure Grade
Slip Resistance	
Wall Mass Inc Hollow	199
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	Yes
Declare	No
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	60 to 240 (see notes)
Integrity	60
Insulation	60

Notes

Maximum slenderness ratio (srf) unreinforced masonry from AS3700:2018 Table 6.1 is: 18.0 at 60 minutes | 17.0 at 90 minutes | 16.0 at 120 minutes | 15.5 at 180 minutes | 15.5 at 240 minutes. This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf 36: 240 minutes